





HT Stepper: (180 °C)



Item	Specification	Item	Specification
Phase Number	2	Step Angle	1.8° ± 5%
Rated Voltage	DC 2.1V / Phase	Rated Current	DC 1.0A / Phase
Phase Resistance	2.1x(1±15%) Ω	Phase Inductance	1.5x(1±20%) mH
Holding Torque	100mN-m	Detent Torque	10 mN-m REF.
Rotate Direction	ACBDA CW	Insulate Resistance	100Mohm(DC500V)
HI-POT	AC600V/1mA/1S	Insulation Class	Class H 180°C
Rotor Inertia	16 g-cm² REF	Weight	85 g REF

B	----	Shaft Length increased from 6 to 6.5	J.B.	J.B.	10/19/23
A	----	NEW RELEASE	J.B.	J.B.	5/8/23
REV.	ECN NO.	DESCRIPTION	MADE BY	APPR. BY	DATE
		VIEW	LDO Motors Co., Ltd. Part NO. 1.8° 36mm Round Pancake Stepper LDO-36STH20-1004AHIG(6T)		
		SCALE	NA		
DRAWN BY	CHECKED BY	APPR. BY	DATE	FACTORY CODE	SHEET NO.
Xu SD	J.B.	J.B.	5/8/23		1/1